

ENERGY ADVANTAGE™

MULTI-LOAD SOFT-MOUNT WASHERS

MXS20PN, MXS25PN, MXS30PN, MXS40PN, MXS55PN, MXS65PN

OPL MARKET

Introducing the new Maytag Commercial Laundry Energy Advantage™ Multi-Load Soft-Mount Washers, the next generation of multi-load washers built for the demands of today and tomorrow.



Faster Spin

- 400 G spin speed extracts more water resulting in faster dry times



Better Energy and Cleaning Performance

- TurboWash™ System spray baffles and tumble patterns provide optimal water savings and cleaning



Easy-to-Use Controls

- 20 preset wash programs
- Multiple language options



USB Programmability

- Easy uploads and downloads of machine settings and software



New Door Design

- Larger door opening and 180-degree door swing allows for easier loading and unloading
- Oversized ergonomic door knob for easy opening
- Durable integrated door hinges



Model MXS40PN shown.



Visit maytagcommerciallaundry.com

WHAT'S INSIDE MATTERS™

MY140245 8/14

ENERGY ADVANTAGE™ MULTI-LOAD SOFT-MOUNT WASHERS

MXS20PN, MXS25PN, MXS30PN, MXS40PN, MXS55PN, MXS65PN

OPL MARKET

WASHER SPECIFICATIONS								
MODEL	MXS20PNATS	MXS25PNATS	MXS30PNATS	MXS40PNATS	MXS55PNARS	MXS55PNATS	MXS65PNARS	MXS65PNATS
MOTOR								
Inverter Drive	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Variable Speed	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
HP (kw)	1.0 (0.75)	1.5 (1.1)	2.0 (1.5)	3.0 (2.2)	4.0 (3.0)	4.0 (3.0)	4.0 (3.0)	4.0 (3.0)
Voltage	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	440–480V Three-Phase	208–240V Single-Phase or Three-Phase	440–480V Three-Phase	208–240V Single-Phase or Three-Phase
BREAKER SIZE—AMPS								
	15A	15A	20A	20A	15A	20A	15A	20A
SPEED								
Extract Speed—Max rpm	1165	1075	1075	980	980	980	915	915
Extract Speed—Max g-force	400	400	400	400	400	400	350	350
LIQUID SOAP SIGNALS								
	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USB PROGRAMMABILITY								
	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
WATER INLET/HOSE								
Water Inlet—in.	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4
Operating Pressure—psi /bar	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8
Drain Size Diameter—in. (mm)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)
CAPACITY								
Lbs. (kg)	20 (9)	25 (11)	30 (14)	40 (18)	55 (24)	55 (24)	65 (28)	65 (28)
Cylinder Volume—cu. ft. (liters)	2.65 (75)	3.71 (105)	4.77 (135)	6.36 (180)	8.48 (240)	8.48 (240)	9.89 (280)	9.89 (280)
Cylinder Diameter—in. (mm)	20.87 (530)	24.4 (620)	24.4 (620)	29.53 (750)	29.53 (750)	29.53 (750)	29.53 (750)	29.53 (750)
Cylinder Depth—in. (mm)	13.39 (340)	13.71 (348)	17.63 (448)	16.05 (408)	21.40 (544)	21.40 (544)	24.95 (634)	24.95 (634)
COLOR								
Front Panel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Side Panels	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray
APPROXIMATE WEIGHT								
Crated—lbs. (kg)	441 (200)	518 (235)	606 (275)	871 (395)	992 (450)	992 (450)	1135 (515)	1135 (515)
Uncrated—lbs. (kg)	408 (185)	463 (210)	563 (255)	838 (380)	948 (430)	948 (430)	1092 (495)	1092 (495)
DIMENSIONS								
Height—in. (mm)	44.83 (1139)	49.16 (1249)	49.16 (1249)	56.45 (1434)	56.45 (1434)	56.45 (1434)	56.45 (1434)	56.45 (1434)
Width—in. (mm)	27.95 (710)	31.29 (795)	31.29 (795)	38.18 (970)	38.18 (970)	38.18 (970)	38.18 (970)	38.18 (970)
Depth Including Handle and Vent on Back—in. (mm)	31.10 (790)	31.29 (795)	37.20 (945)	38.18 (970)	43.50 (1105)	43.50 (1105)	46.65 (1185)	46.65 (1185)
Floor to Bottom of Door—in. (mm)	13.74 (349)	13.46 (342)	13.46 (342)	18.77 (477)	18.77 (477)	18.77 (477)	18.77 (477)	18.77 (477)
Floor to Drain Outlet Center—in. (mm)	3.46 (88)	3.46 (88)	3.46 (88)	4.27 (109)	4.27 (109)	4.27 (109)	4.27 (109)	4.27 (109)
Side to Drain Outlet Center—in. (mm)	9.05 (230)	9.05 (230)	9.05 (230)	10.62 (270)	10.62 (270)	10.62 (270)	10.62 (270)	10.62 (270)
Door Opening Diameter—in. (mm)	12.99 (330)	16.14 (410)	16.14 (410)	18.11 (460)	18.11 (460)	18.11 (460)	18.11 (460)	18.11 (460)

See specific instructions for proper installation.



Three-Year Limited Warranty on Parts. For the first three (3) years from the date of purchase, when this commercial appliance is installed, maintained and operated according to the instructions attached to or furnished with the product, Maytag Commercial Laundry brand of Whirlpool Corporation (hereafter “Maytag”) will pay for factory-specified parts or original equipment manufacturer parts to correct defects in materials or workmanship.

Fourth- and Fifth-Year Limited Warranty on Certain Parts. In the fourth and fifth years from the date of purchase, Maytag will pay for the following washer parts: the outer shell, drum and shaft assembly, inner welded frame, and bearings and seals. See complete warranty for details.